





Linethrower 250

Item Nos. Complete unit 9502000 · Body and line 9500700 · Rocket 9500800

A self-contained line-throwing appliance consisting of a weatherproof plastic casing with end cap, twist-grip trigger assembly, rocket and line. To comply with SOLAS requirements, four complete rocket and line assemblies (Item No. 9502000) should be carried on board. The device has a throwing range of between 230m and 250m. A solid propellant is used which guarantees a highly accurate flight path even in strong sidewinds.

Application

The Pains Wessex 250 is designed for ease of operation in the most extreme weather conditions. It can be used in all situations where a line is required to be passed accurately and quickly, these include:

- · All line-throwing operations at sea between vessels, ship-to-shore,
- shore-to-ship and shore based rescue services.
- · Rescue of swimmers in distress.
- · Line carrying across obstacles and rough terrain.

Operation



- 1. Wear Personal Safety Equipment (gloves, glasses, ear protection, helmet).
- 2. Remove the front cover and point in the desired flight direction.
- 3. Pull out safety pin.
- 4. Aim over the top of target. Be prepared for recoil.
- 5. Turn grip to left or right to fire.
- 6. If misfire occurs hold unit in firing position for at least 60 seconds, then dispose of overboard.

Product Life

- Body and line kit: 9 years
 Rocket minimum 3.5 years
- · Spare rockets are available to replace consumed or time expired rockets.


Packing & Transport Information

Body and Line, less rocket in packing case,

- L 37 cm (14.57 in) x W 27 cm (10.63 in) x H 27 cm (10.63 in)
- Gross weight 4.2 kg (9.26 lb.) Net weight 3.6 kg (7.94 lb.)
- · Other Information: Non-hazardous
- 20 Spare Rockets in metal tin in a fibreboard box,
- L 37 cm (14.57 in) x W 27 cm (10.63 in) x H 27 cm (10.63 in)
- Gross Weight Max: 13 kg (28.66 lb.) Net Weight Max: 10.70 kg (23.59 lb.)
- Net Explosive Content per box : 2.12 kg (4.67 lb.)
- Hazard class 1.4G UN 0431 Proper shipping name: Articles, Pyrotechnic
- Other Information: Cargo Aircraft Only

Specifications

- Projects a line to a nominal range of 250m in calm conditions.
- Length: 33 cm (13.0 in)
- Height: 31.3 cm (12.3 in)
- Diameter: 20.5 cm (8.1 in)
- Gross Weight: 4.7kg (10.36 lb.)
- Net Weight: 4.4 kg (9.7 lb.)
- Rocket Weight Max: 535g (18.9 oz.)
- Explosive Content Max.: 106g (3.74 oz.)
- Line breaking strain: >2 kn



Storage

This compact appliance is ideally stored in a water-resistant locker at ambient temperature allowing easy access in an emergency. The set of 4 appliances normally carried onboard can be dispersed in strategic positions throughout the vessel.

Approvals

Conforms to: BAM 0589-P2-0016 (Complete Unit), 0589-P2-0094 (Rocket only), SOLAS 74 as amended, IMO resolutions MSC. 81(70) Part 1, (MED) 96/98/EC, BGV 424.003, USCG - and other major maritime authorities worldwide

WARNING

- · Ejects rocket projectile do not point at people or property • Do not fire in a confined space
- Keep out of reach of children
- · For emergency use at sea
- · Keep away from source of heat

· Do not dismantle

· Do not use after expiry date

· If damaged or dented do not use

DISPOSAL

• Pyrotechnics must be treated as hazardous items and must be disposed of responsibly in accordance with local regulations. For help and advice, visit our website www.painswessex.com