

## Dräger PointGard 2720 Detection of carbon dioxide

The Dräger PointGard 2720 is a self-contained gas detection system for the continuous area monitoring of carbon dioxide (CO<sub>2</sub>) in ambient air. PointGard 2720's rugged, water-resistant housing comes complete with a horn and strobes, a built-in power supply, and is compatible with a remotely mounted Dräger PIR 7200 infrared CO<sub>2</sub> sensor.



## Benefits

---

### Uses the Dräger PIR 7200 high performance infrared CO<sub>2</sub> sensor

With its stainless steel 316L enclosure and drift free optics, the Dräger PIR 7200 is designed for the harshest industrial and commercial outdoor environments. The unique 4 beam signal stabilizing system makes the sensor resistant to dust or dirt deposits on the optical surfaces. Environmental and ageing effects are largely compensated ensuring long term, drift free operation. The measuring range can be freely adjusted between 0 – 2,000 ppm and 0 – 30% volume enabling a wide variety of applications.

---

### Waterproof stainless steel IR sensor

Thanks to its innovative splash guard and waterproof enclosure, the PIR 7200 sensor is ready for extreme conditions such as areas with daily high-pressure wash-downs and extreme temperature and humidity levels. It is available with an integrated Ex e junction box or an aluminum or 316L stainless steel junction box.

---

### Flexible communications

PointGard can accommodate additional external alarm devices through its three built-in relays. In addition, a 4–20 mA signal with HART output allows integration into a larger gas detection system.

---

### Rugged and compact housing

PointGard's glass fiber reinforced polyester housing is water and dust resistant with a 4X/IP66 rating. Its compact size allows it to easily fit most applications. Built-in cable glands make it easy to install.

---

### Advanced display with diagnostics

The large, illuminated backlit graphic display shows status information clearly and in a format that's easy to interpret. The measured gas concentration, selected gas type, and measuring unit are displayed during normal operation. Coloured LEDs (green, yellow, and red) provide additional alarm and status information. Advanced diagnostics log events and gas readings, which can be displayed and a graph created on the display.

---

### Monitor remote areas up to 30 meters away

The Dräger PIR 7200 sensor is designed to be installed in Zone 1 classified hazardous areas remotely from the PointGard 2720 with a four-conductor shielded cable up to 30 meters long. The cable and Dräger PIR 7200 sensor must be ordered separately from the PointGard 2720.

## Accessories



ST-11680-2007

### Remote sensor Dräger PIR 7200 (M25) complete set

The Dräger PIR 7200 can be placed up to 30 meters away from the PointGard 2720. The type of protection Ex e allows operation in hazardous areas (see approvals). Please note that the shielded four-wire cable is not included.



D-1049-2020

### Remote sensor Dräger PIR 7200 (NPT) complete set

The Dräger PIR 7200 can be placed up to 30 meters away from the PointGard 2720. The Ex d type of protection allows operation in hazardous areas (see approvals). Please note that the shielded four-wire cable is not included.

## Related Products



D-7350-2016

### Dräger PointGard 2100

The Dräger PointGard 2100 is a self-contained gas detection system for the continuous area monitoring of toxic gases in ambient air. PointGard 2100's rugged, water-resistant housing comes complete with a horn and strobes, a built-in power supply, and reliable DrägerSensor®.

## Technische Daten

Dräger PointGard 2720 IR	Carbon dioxide (CO <sub>2</sub> ) in ambient air			
Type	Self-contained gas monitor with alarm devices for general-purpose applications			
Measuring range	0 – 2000 ppm; 0 – 30 Vol.-%			
Display and controls	Display	Graphic LC-Display 75 mm/3 inch Red or green backlight selectable, alphanumeric		
	Indicator	3 status LEDs (green/yellow/red), 85 dB – 100 dB adj. piezo horn		
	Operation	Through three front mounted push buttons		
	Security	Separate passwords for maintenance and configuration menu		
	Functions	Event and data logger with a capacity of up to 35,000 records		
		Warning and error messages displayed in plain text		
Passwordless bump-test mode inhibits alarms				
		Automatic calibration mode for zero and span		
Electrical data	Signal output analog	Normal operation	4–20 mA	
		Maintenance	Constant 3.4 mA or 4 mA ±1 mA 1 Hz modulation (adjustable)	
		Fault	<1.2 mA	
	Power supply AC version	Operating voltage	100–240 VAC 50–60 Hz	
		Nominal power	12 W	
		Operating current (max)	0.5 A	
		Inrush current	Max. 40 A at 230 VAC 50 Hz	
		Power supply DC version	Operating voltage	8–30 VDC
	Nominal power		12 W	
	Operating current (max)		2.5 A	
	Electrical certification	CE rating, IEC/EN 61010-1		
		Complies with UL 61010-1		
		Class B device, residential use compliant with ICES-3(B)/NMB-3(B)		
	Relay specification	2 alarm relays and 1 fault relay SPDT contact 5 A @ 230 VAC, 5 A @ 30 VDC, resistance bound Alarm reset through front-mounted push button		
	Alarm devices	Variants with amber and red LED strobes activate on 2 alarm levels independently		
		Variants with green steady light activate red strobe on 1 common alarm level. Green steady light turns off during alarm or fault condition; optional blue LED strobe		
		85-105 dB adjustable-volume buzzer with continuous and pulsating tone		
	Environmental conditions (see Dräger PIR 7200 data sheet))	Temperature (storage)	-20 to +65 °C/-4 to +149 °F	
		Temperature (operation)	-20 to +50 °C/-4 to +122 °F	
		Humidity	0 to 95% r. h., noncondensing	
Pressure		20.7 to 38.4" Hg/700 to 1,300 hPa		
Housing	Material	Glass fiber reinforced polyester (GFRP)		
	Mounting	Wall mount with internal screws or optional SS mounting brackets		
	Housing protection type	IP66 (pending); indoor or outdoor use		
	Housing protection type	UL 508A/50/50E; CSA C22.2 94.1/94.2/14–13		
	Cable entry point	3 cable glands, M20		
	Size (L x W x D)	255 x 280 x 120 mm/10 x 11 x 4.7"		
	Weight	2,3 kg w/o sensor		

## Ordering Information

### Dräger PointGard 2720 IR (Order Dräger PIR 7200 sensor separately)

Dräger PointGard 2700/2720 IR AC Remote	37 06 858
Dräger PointGard 2700/2720 IR DC Remote	37 06 859
Dräger PointGard 2700/2720 IR AC Remote w/ green light	37 06 860

### Dräger PointGard 2720 IR compatible Sensors

Dräger PIR 7200 (NPT) HART®, complete Set (Stainless Steel)	68 13 055
Dräger PIR 7200 (M25) HART®, complete Set (Stainless Steel)	68 12 290
Dräger PIR 7200 (NPT) HART®, complete Set (Aluminum)	68 13 050

The complete set includes the Ex d or e junction box, the splash guard, the status indicator and the mounting set, already pre-assembled.

### Dräger PointGard 2000 Series Common Accessories

Mounting Bracket Set (not included in Dräger PointGard)	83 26 497
IR Connection Kit for PC configuration and upgrades	45 44 197
LED steady light, green	83 26 489
LED strobe light, blue	83 26 472
AC Power Cable Brazil	83 26 448
AC Power Cable Europe	83 26 449
AC Power Cable UK	83 26 450
AC Power Cable USA	83 26 451
AC Power Cable Australia	83 26 452

HART® is a registered trademark of the HART Communication Foundation.

## Notes

## Notes

## Notes

Not all products, features, or services are for sale in all countries.  
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to [www.draeger.com/trademarks](http://www.draeger.com/trademarks) to find the current status.

### **CORPORATE HEADQUARTERS**

Drägerwerk AG & Co. KGaA  
Moislinger Allee 53–55  
23558 Lübeck, Germany

[www.draeger.com](http://www.draeger.com)

### **REGION EUROPE**

Dräger Safety AG & Co. KGaA  
Revalstraße 1  
23560 Lübeck, Germany  
Tel +49 451 882 0  
Fax +49 451 882 2080  
[info@draeger.com](mailto:info@draeger.com)

### **REGION MIDDLE EAST, AFRICA**

Dräger Safety AG & Co. KGaA  
Branch Office  
P.O. Box 505108  
Dubai, United Arab Emirates  
Tel +971 4 4294 600  
Fax +971 4 4294 699  
[contactuae@draeger.com](mailto:contactuae@draeger.com)

### **REGION ASIA PACIFIC**

Draeger Singapore Pte. Ltd.  
61 Science Park Road  
The Galen #04-01  
Singapore 117525  
Tel +65 6872 9288  
Fax +65 6259 0398  
[asia.pacific@draeger.com](mailto:asia.pacific@draeger.com)

### **REGION CENTRAL AND SOUTH AMERICA**

Dräger Indústria e Comércio Ltda.  
Al. Pucurui - 51 - Tamboré  
06406-100 - Barueri - SP  
Tel. +55 (11) 4689-4900  
[relacionamento@draeger.com](mailto:relacionamento@draeger.com)

Locate your Regional Sales  
Representative at:  
[www.draeger.com/contact](http://www.draeger.com/contact)

