Datasheet LIFE RAFT/RESCUE BOAT HOOK PXOI



The T-ISS Life Raft/Rescue Boat Hook is a combined automatic release hook which can handle rescue boats and life rafts up to a safe working load of 35kN.

The advantage of using the T-ISS PX01 is two-fold;

• It will increase safety, as the crew only need to familiarize themselves with one hook, instead of two. Also there is no second hook, dangerously swinging around when lowering. In distress situations the crew will instantly know which hook to use, as there is only one hook.

• Secondly it is economical, why buy two hooks if one is sufficient?

Pictures




T-ISS

Dimensions	Certificates & Standards
Art.no: PX01	Approved by: EC Directive 96/98EC on Marine Equipment (MED)
Dimensions: 285x260x70 mm	Relevant standard: LSA Code for Hooks for Life raft Launching, as amended MSC.81(70) Fully compliant with updated SOLAS requirements as per Resolutions MSC.320(89) and MSC.321(80)

This hook can be used for rescue boats with a davit load less than 3500 kg and/or a davit launched life raft up to 40 pax. The hook can be operated as an automatic release hook, releasing when the craft enters the water, or as a manual release hook, whereby the load needs to be off the hook before releasing.

Specifications

Weight: approx. 7 kg Maximum Safe Working Load: 3500 kg Material: Stainless steel 316/Duplex



Applications & Use

F +31(0) 315 65 60 63 7091 HR Dinxperlo E info@t-iss.com The Netherlands I t-iss.com Europe

