

3 AA BATTERIES

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

XPP-5422BA, XPP-5422GA



## DUAL-LIGHT

240-lumen Dual-Light provides simultaneous **flashlight and floodlight** operation

IP-67  
DUST/WATER  
PROOF


ZONE 0

CLASS I  
DIV 1

XPP-5422GA



Simultaneous **flashlight and floodlight** operation



Sharp focused flashlight beam



Durable polymer body is **impact & chemical resistant**



Large, textured buttons



AVAILABLE IN MULTIPLE  
COLORS

XPP-5422BA



240 LUMENS

1-800-233-2155 · 1-469-326-9400 · [nightstick.com](http://nightstick.com)

# INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

**3 AA BATTERIES (not included)**

**ITEM NUMBER/UPC**

- XPP-5422BA, UPC 0 1739880807 1
- XPP-5422GA, UPC 0 1739880808 8

**MARKET APPLICATIONS**

- Hazardous work environments, industrial, fire and rescue

**CERTIFICATIONS**

- cETLus, ATEX, IECEx, CE, InMetro

**CASE MATERIAL**

- Engineered polymer

**LUMENS/RUNTIME**

**FLASHLIGHT**

- 120L, 17.5 hrs. runtime

**FLOODLIGHT**

- 120L, 17.5 hrs. runtime

**DUAL-LIGHT**

- 240L, 4.5 hrs. runtime

**CANDELA**

- 7,250

**BEAM DISTANCE**

- 170 m

**WATER RATING**

- ANSI IP-67 dustproof / waterproof

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 7.0 in (178 mm)
- HANDLE DIAMETER: 1.1 in x 1.5 in (28 mm x 38 mm)
- HEAD DIAMETER: 1.8 in (46 mm)
- WEIGHT: 6.9 oz (196 g)

**POWER SOURCE**







- AA batteries (not included)

**WARRANTY**

- Limited lifetime

**WHAT'S INCLUDED**

- Flashlight
- Removable lanyard
- Instruction manual

FL 1 STANDARD	SPOT	FLOOD	DUAL-LIGHT
	<b>120 LUMENS</b>	<b>120 LUMENS</b>	<b>240 LUMENS</b>
	<b>17h</b>	<b>17h</b>	<b>4h 30min</b>
	<b>170m</b>		
	<b>7250cd</b>		
	<b>2m</b>		
	<b>1m</b>		

**Bayco Products, Inc. XPP-5422BA**  
 640 S. Sanden Blvd.  
 Wylie, TX 75098



Intertek



ID 4003544  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3  
 CLASS II & III DIV 1 GRPS E-G T135C  
 CLASS I ZONE 0 AEx ia IIC T3 Ga  
 CLASS I ZONE 0 Ex ia IIC T3 Ga  
 Ⓢ I M 1 Ex ia op is I Ma  
 Ⓢ II 1 G Ex ia op is IIC T3 Ga

Ex ia op is I Ma  
 Ex ia op is IIC T3 Ga  
 Intertek ITS 13 ATEX27837X  
 IECEx ITS 16.0067X  
 -20°C ≤ Tamb ≤ +40°C  
 1.5V/Cell AA Alkaline



**Conforms to:**  
 ANSI/UL STD 913, ANSI/UL 60079-0,  
 ANSI/UL 60079-11 ANSI/ISA 60079-26

**Certified to:**  
 CAN/CSA STD C22.2 No 157  
 CAN/CSA STD C22.2 No 60079-0  
 CAN/CSA STD C22.2 No 60079-11  
 CSA STD C22.2 No 25

CERTIFIED



© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPP-5422A Series-Z1

